

Take-Off 4T HD 10W-50

Synthetic High Performance4-Stroke Motorcycle Engine Oil

TECHNICAL DATA SHEET

Product Description:

Veedol Take-Off 4T HD 10W-50 is a synthetic high performance 4-stroke motorcycle engine oil developed especially for high performance modern generation motorcycles.

Veedol Take-Off 4T HD 10W-50 is formulated using premium quality base oils fortified with specially selected additives that provides outstanding engine performance and excellent wear protection at high temperatures.

Veedol Take-Off 4T HD 10W-50 delivers exceptional performance under severe operating conditions in all seasons and driving environments

Performance Specifications:

Meets & Exceeds the performance requirements of

- API SN
- JASO MA2 (T903:2016)

Features/Benefits:

- Retains adequate film thickness at extreme temperatures providing reduced frictional losses.
- Excellent oxidation and thermal stability for longer service periods
- Outstanding low temperature properties help easy cold starting.
- Excellent protection against wear, rust and corrosion.
- Delivers superior acceleration with unmatched smoothness.

Application:

Recommended for all four-stroke modern generation engines of high performance motorcycles.

Typical Properties:

Test Parameter	ASTM Test Method	Typical Value
Kinematic Viscosity, @ 100°C, cSt	ASTM D 445	18.5
Viscosity Index	ASTM D 2270	155
Flash Point (COC), °C	ASTM D 92	250
Pour Point, °C	ASTM D 97	-33
CCS Viscosity @-25°C, mPa.s	ASTM D 5293	5680

Properties mentioned above are typical only and minor variations which do not affect the product performances, are to be expected in normal manufacturing.