

VEEDOL ATF 8HP

Description

Veedol ATF 8HP is a premium automatic transmission fluid formulated using specially selected synthetic base oils with a high viscosity index and performance additives to achieve the following properties:

- Improves fuel economy.
- Provides excellent lubrication
- A very high oxidation and thermal stability
- Excellent and stable friction characteristics for longer oil replacement intervals.
- Excellent resistance against foaming.
- Excellent protection against wear
- A very high and stable viscosity index
- Green coloured

Features & Benefits

Veedol ATF 8HP is a specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly towards fuel saving and can be used for other ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, in various VAG models.

Performance Specifications

Meets the requirements of the following;

VAG G-060-162
 BMW 8322 2152426
 Jaguar 02JDE 26444
 Land Rover LR023288
 Chrysler 68157995AA
 Fiat 9.55550-AV5

Typical Properties

Density at 15 °C, kg/l	0.845
Viscosity 40 °C, mm ² /s	25.80
Viscosity 100 °C, mm ² /s	6.00
Viscosity Index	190
Pour Point, °C	-45

Veedol International B.V.

Kabelweg 21, 1014 BA Amsterdam, The Netherlands

TM

Registered trademarks of Veedol International UK

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.