



VEEDOL SYNTRON RACING 10W-60

Description

Veedol Synttron Racing is fully synthetic motor oil, blended using high quality synthetic base oils and advanced additives system to achieve following properties:

- Very high & stable viscosity index for complete lubrication.
- High viscosity oil maintains optimum lubrication film thickness even at high temperatures.
- Exhibits excellent resistance against shearing.
- Provides fast response even at low temperatures.
- Very good detergency and dispersion properties keep engine interior clean and fuel efficient.
- Provides strong protection against wear, corrosion and foaming.

Features & Benefits

Veedol Synttron Racing is high quality synthetic motor oil recommended for use in passenger cars operating under most arduous conditions including racing competitions.

Performance Specifications

Meets the requirements of the following;

ACEA A3/B4
API SL/CF

Typical Properties

Density at 15 °C, kg/l	0.854
Viscosity -25 °C, mPa.s	6190
Viscosity 40 °C, mm ² /s	163.30
Viscosity 100 °C, mm ² /s	23.30
Viscosity Index	173
Flash Point COC, °C	224
Pour Point, °C	-40
Total Base Number, mgKOH/g.....	10.5
Sulphate Ash, %	1.33

Veedol International B.V.

Kabelweg 21, 1014 BA Amsterdam, The Netherlands

TM

Registered trademarks of Veedol International UK

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.