



VEEDOL MULTIGRADE SPECIAL 15W- 50

Description

Veedol Multigrade Special 15W-50 engine oil is blended from top quality base stocks and premium performance additive package to meet the exact balanced dispersant, high temperature detergents, antioxidant, anti corrosion, anti wear properties. It is a high rated diesel engine oil capable of meeting severe duty conditions. It conforms to API CF-4 performance standards

Veedol Multigrade Special 15W-50 is recommended for use in all turbo charged or super charged diesel engines working at high speeds and high load/severe duty conditions and burning different quality of diesel fuels; all Caterpillar engines and Naturally aspirated diesel engines.

Properties

Higher oxidation stability leading to reduced high temperature deposits.
Reduced fuel consumption
Long engine life and engine overhaul intervals.
TBN retention for longer periods
Extended oil drain period
Lower oil consumption.
Prevent ring sticking and reduces ring wear and bore polishing

Performance & Specifications

Meets the requirements of the following

API CF4/CF/SJ
ACEA E2
MB 228.1
MAN 271
MTU Oil Type 1
VOLVO VDS

Typical Properties

Density at 15 °C, kg/l	0.886
Viscosity 40 °C, cSt	130.0
Viscosity 100 °C, cSt	18.00
Viscosity Index	154
Flash Point °C	222
Pour Point, °C	-30
TBN, mg/KOH/gm	11.00
Apparent Viscosity at 20°C, mPa	5500

Veedol International DMCC

Unit 601, Indigo Icon, Jumeirah Lakes Towers
P.O. Box No. 117019, Dubai, U.A.E.

TM

Registered trademarks of Veedol International UK

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.