



VEEDOL Rapid Kool

Product Description

Veedol Rapid Kool is an ethylene glycol based engine coolant concentrate, which uses Organic Acid Inhibitor Technology (OAT) and is free from nitrates, amines, phosphates, borates and silicates. **Veedol Rapid Kool** has a 5 year or 250,000km life and should be changed whichever is the sooner. Unlike traditional coolants which employ inorganic inhibitors, **Veedol Rapid Kool** has excellent hard water stability and very low inhibitor depletion rates.

Product Benefits

- 5 Year protection
- Organic Acid Technology
- Ethylene Glycol based
- BS6580: 2010

Directions for Use

As recommended by the engine manufacturer

Dosage Information

Freeze Protection:

- 12°C @ 25% concentration by volume
- 22°C @ 33% concentration by volume
- 40°C @ 50% concentration by volume

Specification Information

Exceeds the requirements of: ASTM D3306, ASTM D 4985, SAE J 1034, BS 6580 (2010), AFNOR NF R15-601, JIS K2234, NATO S 759, FFV Heft R443, CUNA NC956-16, UNE26361-88.

Meets the requirements of: Chrysler MS 9176, Cummins 85T8-2 & 90T8-4, Ford ESE M97B49-A, WSS-M97B44-D & ESD M97 B49-A, GM 1899M, John Deere H 24 B1 & C1, Leyland Trucks LTS 22 AF 10, Mack 014GS 17004, MAN 248,324 (SNF) & B&W D 36 5600. Mercedes MB 325.3, Renault 41-01-001, VAG TL 774D/F, Volvo

Storage Instructions

Store sealed in a cool, dry place

Shelf Life

3 Years from date of manufacture

Typical Properties

Appearance	: Pink/Red liquid
Odour	: Odourless
Specific Gravity	: 1.119 (Typical)
Solubility	: Miscible in water
Flashpoint	: 111°C

Manufactured under the authority of Veedol International Limited, UK

Granville Oil and Chemicals Ltd.

29 Goldthorpe Industrial Estate, Goldthorpe, Rotherham, S63 9BL, England

TM

Registered trademarks of Veedol International UK

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.