VEEDOL SYNTRON C3 5W-40

Description

Veedol Syntron C3 5W-40 is a fully synthetic motor oil, blended from premium synthetic base oils and hi-tech performance additives to achieve following properties:

- Very high and long lasting shear stable viscosity index for complete lubrication at all operating temperature extremes.
- Optimum lubricating film at high temperatures.
- Low pour point for quick response even at low temperatures.
- Very good detergency and dispersion provides excellent engine cleanliness.
- Very high oxidation stability offers consistent performance with longer life.
- Very strong protection against wear, corrosion and foaming.
- Reduction in formation of combustion gases.

Features & Benefits

Veedol Syntron C3 5W-40 is high quality synthetic motor oil recommended for use in modern generation passenger cars with turbo charged/supercharged engines.

Performance Specifications

Meets the requirements of the following:

ACEA C3
API SN/CF
VW 502.00/505.00/505.01
MB-229.31/229.51/226.5
BMW Longlife-04
Ford WSS-M2C917-A
Porsche A40
Dexos 2
Fiat 9.55535-S2

Typical Properties

Viscosity @ 40°C, mm²/s …………………………… 88.64
Viscosity @ 100°C, mm²/s ………………………... 13.91
CCS ……………………………………………… 6201
Viscosity Index ………………………………………... 161
Pour Point, °C ……………………………………… -39
Flash Point, °C ..……………………………………… 226

Granville Oil and Chemicals Ltd
Goldthorpe Industrial Estate, Goldthorpe, Rotherham, S63 9BL, England